




FIRE/POLICE/RESCUE SYSTEMS

EQUIPMENT STORAGE • HOLDING CELLS • KITCHENS • VEHICLE BAYS















EQUIPMENT STORAGE


SIMFLAKE SB DECORATIVE CHIP

First responders may drop equipment when it is pulled quickly or put away. **SIMFLAKE SB** is a decorative system utilizing a full broadcast of **Simiron Decorative Chip** that is available in multiple blends to achieve a durable surface with long-lasting results. The texture resulting from the broadcast is critical to minimize slip on floors when gear that may be wet is put away. This three-step system consists of a primer, basecoat/broadcast, and a polyaspartic topcoat.


SYSTEM ATTRIBUTES

 DURABLE: 30 mg loss	 ADHESION: > 400 psi	 COEFFICIENT OF FRICTION: > .55	 COMPRESSIVE STRENGTH: 11,600 psi	 ELONGATION: 5 - 10%	 FLAMMABILITY: Self-extinguishing on concrete
 FLEXIBILITY 1/8" BEND MANDREL: PASS	 FLEXURAL STRENGTH: 12,800 psi	 GLOSS: 92 - 95°	 HARDNESS: Shore D > 70, 86	 TENSILE STRENGTH: > 9,600 psi	 UV RESISTANT

SYSTEM BUILD



COLOR SELECTIONS















To view all color selections refer to the **Simiron Product Color Guide**.

HOLDING CELLS


SIMFLOOR EPOXY SILOXANE CHEMICALLY RESISTANT

There is no telling what detained people may do to the floor and walls in a holding area. **SIMFLOOR EPOXY SILOXANE** is a chemical-resistant floor system that offers maximum surface protection found in environments of this nature. The recommended satin finish topcoat with low odor and VOC offers excellent abrasion resistance. Optional non-skid texture and a gloss version are also available.

SYSTEM ATTRIBUTES


 ADHESION: > 400 psi	 COEFFICIENT OF FRICTION: .50	 COMPRESSIVE STRENGTH: 11,600 psi	 ELONGATION: 5 - 10%	 FLAMMABILITY: Self-extinguishing on concrete	 FLEXIBILITY 1/8" BEND MANDREL: PASS
 FLEXURAL STRENGTH: 12,800 psi	 HARDNESS: Shore D: 75	 GLOSS: 88°	 TABER ABRASION: 40 mg loss	 TENSILE STRENGTH: 9,600 psi	 UV RESISTANT

SYSTEM BUILD



COLOR SELECTIONS

To view all color selections refer to the **Simiron Product Color Guide**.
















SIMCRETE SL


URETHANE CEMENT

SIMCRETE SL is a self-leveling urethane cement installed at 1/8" and broadcast to rejection with silica sand to achieve a 3/16" heavy-duty system with a slip-resistant texture suited for kitchen applications. This extremely durable flooring system withstands thermal shock needed under ovens, oil splatter and the impact from dropped cooking equipment. A polyaspartic is used to lock in the broadcast, which provides UV stability and resistance to any chemicals used to clean kitchens.

SYSTEM ATTRIBUTES


 BOND STRENGTH: 100% Concrete Failure	 COEFFICIENT OF FRICTION: > 0.63	 COMPRESSIVE STRENGTH: 8,558 psi	 FLAMMABILITY: Self-extinguishing on concrete	 FLEXURAL STRENGTH: 2,780 psi	 GLOSS: 92 - 95
 IMPACT STRENGTH: > 160 lbs/inch	 RESISTANCE TO FUNGI GROWTH: PASS	 TABER ABRASION: 30 mg loss	 TENSILE STRENGTH: 1,120 psi	 UV RESISTANT	

SYSTEM BUILD



COLOR SELECTIONS

To view all color selections refer to the **Simiron Product Color Guide**.





VEHICLE BAYS




SIMFLAKE SB DECORATIVE CHIP

The floors behind large glass doors have become a Fire Station showplace. **SIMFLAKE SB** is a 60 mil, decorative system that provides a sound base for heavy trucks and resists UV damage to exposure through the overhead doors. **Simiron Decorative Chip** is utilized in the system and is available in a wide variety of blends that will pair well with any facility color scheme. Optional satin and non-skid textures are available where workers and equipment are loaded and unloaded in areas that may be wet.

SYSTEM ATTRIBUTES

 DURABLE: 30 mg loss	 ADHESION: > 400 psi	 COEFFICIENT OF FRICTION: > .55	 COMPRESSIVE STRENGTH: 11,600 psi	 ELONGATION: 5 - 10%	 FLAMMABILITY: Self-extinguishing on concrete
 FLEXIBILITY 1/8" BEND MANDREL: PASS	 FLEXURAL STRENGTH: 12,800 psi	 GLOSS: 92 - 95°	 HARDNESS: Shore D > 70, 86	 TENSILE STRENGTH: > 9,600 psi	 UV RESISTANT


SYSTEM BUILD



- TOPCOAT:**
POLYASPARTIC HS, GLOSS, CLEAR
- BASECOAT:**
1100SL 100% SOLIDS EPOXY, PIGMENTED & DECORATIVE CHIP
- PRIMER:**
1000HS 100% SOLIDS EPOXY PRIMER, CLEAR
- PREPARED SUBSTRATE:**
CSP 3+

COLOR SELECTIONS

To view all color selections refer to the **Simiron Product Color Guide**.



CHEMICAL RESISTANCE CHART

SIMIRON SYSTEMS	SIMFLAKE SB EPOXY	SIMFLAKE SB POLYUREA	SIMFLOOR HB-EPOXY	SIMFLOOR HWU	SIMFLOOR ESD	SIMFLOOR EPOXY SILOXANE	SHOP FLOOR
CHEMICAL	RESULTS	RESULTS	RESULTS	RESULTS	RESULTS	RESULTS	RESULTS
10% Acetic Acid	G	G	G	F	F	E	G
Vinegar	G	G	G	G	G	G	G
10% Citric Acid	G	G	G	G	G	G	G
10% Hydrochloric Acid	G	G	G	E	E	E	G
30% Hydrochloric Acid (muriatic)	G	G	G	E	E	E	G
10% Nitric Acid	NR	NR	G*	G	G	G	NR
50% Phosphoric Acid	F	F	F	G	G	G	F
10% Sulfuric Acid	F	F	G	F	F	G	F
37% Sulfuric Acid	F	F	F	F	F	G	F
70% Sulfuric Acid	F	F	F	F	F	G*	F
20% Ammonium Nitrate	E	E	E	E	E	E	E
20% Sodium Chloride	E	E	E	E	E	E	E
50% Sodium Hydroxide	G	G	E	E	E	E	G
Methyl Ethyl Ketone	E	E	G	E	E	E	E
Xylene	E	E	F	E	E	E	E
Ethylene Glycol	E	E	G	E	E	E	E
Isopropyl Alcohol	E	E	F	E	E	E	E
Mineral Spirits	F	F	E	E	E	E	F
Brake Fluid	E	E	F	G	G	G	E
Transmission Fluid	E	E	E	E	E	E	E
Motor Oil	E	E	E	E	E	E	E
50:1 Gas/Oil Mixture	E	E	E	E	E	E	E
E85 Gasoline	E	E	E	E	E	E	E
E95 Gasoline	E	E	E	E	E	E	E
Unleaded Gasoline	E	E	G	E	E	E	E
Skydrol	E	E	E	E	E	E	E
Betadine	E	E	G*	G*	G*	G*	E
Bleach	E	E	E	E	E	E	E
Urine	E	E	E	E	E	E	E
Coffee	E	E	E	E	E	E	E
Cola	E	E	E	E	E	E	E
Ketchup	E	E	G	F	F	E	E
Mustard	G*	G*	G	G	G	G*	G*
Red Wine	E	E	E	E	E	E	E

*Stain is only defect.

SIMIRON SYSTEMS	SIMCRETE SL	SIMCRETE SL FLAKE	SIMCRETE SL QUARTZ	SIMQUARTZ DB	SIMCRETE SL+TC	SIMFLOOR METALLIC
CHEMICAL	RESULTS	RESULTS	RESULTS	RESULTS	RESULTS	RESULTS
10% Acetic Acid	G	G	G	F	E	E
Vinegar	G	G	G	F	E	G
10% Citric Acid	G	G	G	E	E	G
10% Hydrochloric Acid	G	G	G	E	E	E
30% Hydrochloric Acid (muriatic)	G	G	G	E	E	E
10% Nitric Acid	NR	NR	NR	NR	G	G
50% Phosphoric Acid	F	F	F	NR	G	G
10% Sulfuric Acid	F	F	F	E	G	G
37% Sulfuric Acid	F	F	F	G	F	G
70% Sulfuric Acid	F	F	F	NR	NR	G*
20% Ammonium Nitrate	E	E	E	E	E	E
20% Sodium Chloride	E	E	E	E	E	E
50% Sodium Hydroxide	G	G	G	G	E	E
Methyl Ethyl Ketone	E	E	E	E	F	E
Xylene	E	E	E	E	E	E
Ethylene Glycol	E	E	E	E	E	E
Isopropyl Alcohol	E	E	E	E	E	E
Mineral Spirits	F	F	F	E	E	E
Brake Fluid	E	E	E	G	E	G
Transmission Fluid	E	E	E	E	E	E
Motor Oil	E	E	E	E	E	E
50:1 Gas/Oil Mixture	E	E	E	E	E	E
E85 Gasoline	E	E	E	E	E	E
E95 Gasoline	E	E	E	E	E	E
Unleaded Gasoline	E	E	E	E	E	E
Skydrol	E	E	E	E	E	E
Betadine	E	E	E	G*	E	G*
Bleach	E	E	E	E	E	E
Urine	E	E	E	E	E	E
Coffee	E	E	E	E	E	E
Cola	E	E	E	E	E	E
Ketchup	E	E	E	F	E	E
Mustard	G*	G*	G*	G	E	G*
Red Wine	E	E	E	E	E	E

*Stain is only defect.

KEY

E = Excellent

G = Good

F = Fair

NR = Not Recommend



SIMIRON.COM | SHOP.SIMIRON.COM



SIMIRON INC.
CORPORATE HEADQUARTERS
3000 Research Drive
Rochester Hills, MI 48309
(248) 686-3600

MADE IN THE USA

